



These instructions and the images herein are proprietary. Any unauthorized reproduction is prohibited.

GVW-025-115-431

EXTERNAL HEX OIL PRESSURE RELIEF PLUG W/ PORT FOR TEMPERATURE SENDER (BUS/VANAGON)

---

### Installation Notes:

- This kit replaces the original slotted oil pressure relief plug in your Bus or Vanagon with a 19mm external hex plug, which makes it much easier to remove.
- If you are NOT using a temperature sender (available separately), you will need to install the provided 1/8" NPT plug into the temperature port on the top of the oil pressure relief plug.
- The 1/8" NPT plug has sealant applied to the male threads to prevent leaks.
- Using a 3/16" internal hex (Allen key), tighten the small plug 3/4 to 1-3/4 turns *past* finger tight. It may be necessary to hold the oil pressure relief plug with a 19mm box-end wrench or place it in a vise to properly tighten the temperature port plug.
- Assemble the plunger, spring, and crush washer on the plug, and insert the assembly into the engine block.
- Tighten the plug to **15 ft-lb. DO NOT OVER-TIGHTEN!**



Oil Pressure Relief Plug, Crush Washer,  
and Temperature Port Plug



Temperature Port Plug Installed

GoWesty Camper Products • 1119 Los Olivos Ave, Los Osos, CA 93402 • 888-469-3789 • www.gowesty.com



These instructions and the images herein are proprietary. Any unauthorized reproduction is prohibited.

GVW-025-115-431

EXTERNAL HEX OIL PRESSURE RELIEF PLUG W/ PORT FOR TEMPERATURE SENDER (BUS/VANAGON)

---

### Installation Notes:

- This kit replaces the original slotted oil pressure relief plug in your Bus or Vanagon with a 19mm external hex plug, which makes it much easier to remove.
- If you are NOT using a temperature sender (available separately), you will need to install the provided 1/8" NPT plug into the temperature port on the top of the oil pressure relief plug.
- The 1/8" NPT plug has sealant applied to the male threads to prevent leaks.
- Using a 3/16" internal hex (Allen key), tighten the small plug 3/4 to 1-3/4 turns *past* finger tight. It may be necessary to hold the oil pressure relief plug with a 19mm box-end wrench or place it in a vise to properly tighten the temperature port plug.
- Assemble the plunger, spring, and crush washer on the plug, and insert the assembly into the engine block.
- Tighten the plug to **15 ft-lb. DO NOT OVER-TIGHTEN!**



Oil Pressure Relief Plug, Crush Washer,  
and Temperature Port Plug



Temperature Port Plug Installed

GoWesty Camper Products • 1119 Los Olivos Ave, Los Osos, CA 93402 • 888-469-3789 • www.gowesty.com