



These instructions and the images herein are proprietary. Any unauthorized reproduction is prohibited

## Pop-top Seal Kit Installation Guide 1993-2003 VW Eurovan Campers



### Luggage Rack Seal (Winnebago Only)

**Removal:** Remove the bolts holding the tie down rods and luggage rack onto the roof brackets and remove the luggage rack. This is also a good time to replace those flimsy, rusted steel brackets that come from the factory with some nice stainless replacements (EVC-LUGGAGE-BRACKETS).

**Installation:** Starting in the middle of the rear of the luggage rack, install the seal with the small sealing bulb around the rack (bulb oriented inwards), tapping it on with a mallet. Trim it to fit flush in the rear and reinstall the luggage rack.

### Pop-top Seal

**Removal:** Remove the old seal with the top in the "up" position. After removal, clean the top edge of the pop-top with soap and water. Remove rust stains with a mild abrasive such as Ajax or Soft Scrub.

**Installation:** Place pop-top in "down" position without latching. Prop up the front edge approximately 6"-12" with a block of wood or cardboard box.

**Winnebago:** Start in the middle of the **FRONT** edge of the pop-top.

**Westfalia:** Start in the middle of the **REAR** edge of the pop-top.

Tap or press the new seal on with the bulb and the "fang" on the inside of the U-channel oriented inward. When you get back around to where you started, trim the seal to sit flush with the other end. You can use some superglue or silicone sealant to seal the two ends of the seal together for a weather tight connection.

GoWesty Camper Products • 1119-A Los Olivos Ave, Los Osos, CA 93402 • 888-469-3789 • [www.gowesty.com](http://www.gowesty.com)



These instructions and the images herein are proprietary. Any unauthorized reproduction is prohibited

## Pop-top Seal Kit Installation Guide 1993-2003 VW Eurovan Campers



### Luggage Rack Seal (Winnebago Only)

**Removal:** Remove the bolts holding the tie down rods and luggage rack onto the roof brackets and remove the luggage rack. This is also a good time to replace those flimsy, rusted steel brackets that come from the factory with some nice stainless replacements (EVC-LUGGAGE-BRACKETS).

**Installation:** Starting in the middle of the rear of the luggage rack, install the seal with the small sealing bulb around the rack (bulb oriented inwards), tapping it on with a mallet. Trim it to fit flush in the rear and reinstall the luggage rack.

### Pop-top Seal

**Removal:** Remove the old seal with the top in the "up" position. After removal, clean the top edge of the pop-top with soap and water. Remove rust stains with a mild abrasive such as Ajax or Soft Scrub.

**Installation:** Place pop-top in "down" position without latching. Prop up the front edge approximately 6"-12" with a block of wood or cardboard box.

**Winnebago:** Start in the middle of the **FRONT** edge of the pop-top.

**Westfalia:** Start in the middle of the **REAR** edge of the pop-top.

Tap or press the new seal on with the bulb and the "fang" on the inside of the U-channel oriented inward. When you get back around to where you started, trim the seal to sit flush with the other end. You can use some superglue or silicone sealant to seal the two ends of the seal together for a weather tight connection.

GoWesty Camper Products • 1119-A Los Olivos Ave, Los Osos, CA 93402 • 888-469-3789 • [www.gowesty.com](http://www.gowesty.com)